PE Flex Full-Vac

Specifications August 2021

Construction: Rugged yellow polyethylene copolymer hose reinforced with an integral polyethylene helix.

Product Features:

- Improved double helix design allows for superior flexibility & durability even in sub-zero temperatures
- Ideal for waste evacuation, septic pumping & sewer cleaning
- Superior abrasion & crush resistance
- All sizes handle a full vacuum
- Smooth interior assures efficient air flow
- Resistant to kinking
- Made with factory-installed leak proof poly-weld cuffs

Applications: Abrasives, Materials.

Temperature Range: - 40 F to + 140 F

Sizes I.D. (inches): 1.50, 2.00, 3.00, and 4.00 inch I.D.

ID Tolerances: -0.00 to +0.050 Inch

Standard Length: 25 & 50 Feet

Standard Colors: Yellow with black web

End Finish: Black leak proof cuffs standard on each end

Markets: Marine Sanitation Hose, Pumper, Sewer & Waste, Suction Hose

Rubber-Cal, Inc. 18424 Mt Langley St, Fountain Valley, CA 92708 800-370-9152 www.ducting.com



PE Flex Full-Vac

Specifications August 2021

		Min		Max	Max
Size	Approximate	Centerline	Compression	Recommended	Recommended
Inside		Bend			
Diameter	Weight	Radius	Ratio	Negative Pressure	Positive Pressure
(Inches)	Lbs./ft.	(Inches)		(IN./HG)	(PSI)
1.5	0.35	3.75	N/A	29	26
2	0.65	5	N/A	29	17
3	1.2	8	N/A	29	12
4	1.6	9.5	N/A	29	7

Note: Technical data based on 2 ft. straight lengths of hose 72 F.

Disclaimer: The proper use and maintenance of the hose and/or duct is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible. Adequate testing under actual service conditions is necessary to properly establish suitability. We take pride in the quality of all of our products and we welcome comments and suggestions from our customers.

Rubber-Cal, Inc. 18424 Mt Langley St, Fountain Valley, CA 92708 800-370-9152

www.ducting.com

