
MATERIAL SAFETY DATA SHEET

===== |
 | SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION |
 ===== |

PRODUCT NAME : CLEAR ADHESIVE
 IDENTIFICATION NUMBER: UK409 DATE PRINTED: 02/03/10
 PRODUCT USE/CLASS :

SUPPLIER: Specialty Coatings & Chemicals Inc 7360 Varna Ave. North Hollywood, CA 91605-4060 Chemtrec: 1-800-424-9300 24 Hour Emergency Hotline	MANUFACTURER: Specialty Coatings & Chemicals Inc 7360 Varna Ave. North Hollywood, CA 91605-4060 Chemtrec: 1-800-424-9300 24 Hour Emergency Hotline
---	---

PREPARER: A.C.Macdonald, PHONE: 323-875-0233, PREPARE DATE: 02/03/10

===== |
 | SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS |
 ===== |

ITEM	CHEMICAL NAME	CAS NUMBER	WT/WT % LESS THAN
01	2-BUTANONE	78-93-3	65.0 %

ITEM	EXPOSURE LIMITS					
	ACGIH TLV-TWA	ACGIH TLV-STEL	OSHA PEL-TWA	OSHA PEL-CEILING	COMPANY TLV-TWA	SKIN
01	200 ppm	300 ppm	200 ppm	N.E.	200 ppm	NO

(See Section 16 for abbreviation legend)

===== |
 | SECTION 3 - HAZARDS IDENTIFICATION |
 ===== |

*** EMERGENCY OVERVIEW ***: No Information.

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Liquid, aerosols and vapors of this product are irritating and can cause pain, tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: No Information.

EFFECTS OF OVEREXPOSURE - INHALATION: No Information.

EFFECTS OF OVEREXPOSURE - INGESTION: This material may be harmful or fatal if swallowed.

|=====|
| SECTION 3 - HAZARDS IDENTIFICATION |
|=====|

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: Over-exposure to powders can cause health effects arising from mechanical effects. These include irritation to the eyes, abrasive irritation to the skin, irritation to the respiratory tract which can cause coughing, sneezing, chest pain and difficulty breathing. Mechanical symptoms arising from excessive ingestion may include discomfort and obstruction of the digestive system.

PRIMARY ROUTE(S) OF ENTRY: SKIN CONTACT SKIN ABSORPTION INHALATION
INGESTION EYE CONTACT

|=====|
| SECTION 4 - FIRST AID MEASURES |
|=====|

FIRST AID - EYE CONTACT: Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

FIRST AID - SKIN CONTACT: Wash with soap and water. Get medical attention if irritation develops or persists.

FIRST AID - INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

FIRST AID - INGESTION: If swallowed, induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

|=====|
| SECTION 5 - FIRE FIGHTING MEASURES |
|=====|

FLASH POINT: 23 F LOWER EXPLOSIVE LIMIT: 2.0 %
(PENSKY-MARTENS C.C.) UPPER EXPLOSIVE LIMIT: 11.5 %

AUTOIGNITION TEMPERATURE:

EXTINGUISHING MEDIA: CO2 DRY CHEMICAL FOAM WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS: Dust clouds comprised of pigment powder can create an explosion hazard. Vapors can travel to a source of ignition and flash back. Extremely Flammable. Material will readily ignite at room temperatures. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner, or properly disposed of.

SPECIAL FIREFIGHTING PROCEDURES: No Information.

```

=====
|
|           SECTION 6 - ACCIDENTAL RELEASE MEASURES
|
=====

```

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container.

```

=====
|
|           SECTION 7 - HANDLING AND STORAGE
|
=====

```

HANDLING: This product is to be used for industrial or professional uses only and is to be applied only by those who are trained in its safe and proper application. Wash thoroughly after handling.

STORAGE: No Information.

```

=====
|
|           SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION
|
=====

```

ENGINEERING CONTROLS: Good general ventilation should be sufficient to control airborne levels. Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product. Use explosion-proof ventilation equipment. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

RESPIRATORY PROTECTION: A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

SKIN PROTECTION: Where contact is likely, wear chemical resistant gloves, a chemical suit, rubber boots, and chemical safety goggles plus a face shield.

EYE PROTECTION: Wear safety glasses with side shields (or goggles) and a face shield.

OTHER PROTECTIVE EQUIPMENT: No Information.

HYGIENIC PRACTICES: Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and wash before reuse. Use only in a well ventilated area. Follow all MSDS/label precautions even after container is emptied because they may retain product residues. Avoid prolonged or repeated contact with skin. Avoid contact with eyes, skin, and clothing.

|=====
| SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES |
|=====

BOILING RANGE : 170 - 175 F VAPOR DENSITY : Is heavier than air
ODOR : Solvent ODOR THRESHOLD :
APPEARANCE : Clear liquid EVAPORATION RATE: Is slower than Ether
SOLUBILITY IN H2O : Partially soluble
FREEZE POINT : SPECIFIC GRAVITY: 0.9486
VAPOR PRESSURE : pH @ 0.0 % :
PHYSICAL STATE : VISCOSITY :
COEFFICIENT OF WATER/OIL DISTRIBUTION:

(See Section 16 for abbreviation legend)

|=====
| SECTION 10 - STABILITY AND REACTIVITY |
|=====

CONDITIONS TO AVOID: No Information.

INCOMPATIBILITY: No Information.

HAZARDOUS DECOMPOSITION PRODUCTS: No Information.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

|=====
| SECTION 11 - TOXICOLOGICAL PROPERTIES |
|=====

No product or component toxicological information is available.

|=====
| SECTION 12 - ECOLOGICAL INFORMATION |
|=====

ECOLOGICAL INFORMATION: No Information.

|=====
| SECTION 13 - DISPOSAL CONSIDERATIONS |
|=====

DISPOSAL METHOD: No Information.

|=====
| SECTION 14 - TRANSPORTATION INFORMATION |
|=====

No transportation information is available.

|=====
| SECTION 15 - REGULATORY INFORMATION |
|=====

U.S. FEDERAL REGULATIONS: AS FOLLOWS -

SECTION 15 - REGULATORY INFORMATION

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

CERCLA - SARA HAZARD CATEGORY:

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

FIRE HAZARD

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

CHEMICAL NAME CAS NUMBER WT/WT % IS LESS THAN
No SARA Section 313 components exist in this product.

TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

CHEMICAL NAME CAS NUMBER
No information is available.

INTERNATIONAL REGULATIONS: AS FOLLOWS -

CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings.

CANADIAN WHMIS CLASS: No information available.

GOVERNMENT REGULATIONS: No Information.

SECTION 16 - OTHER INFORMATION

HMIS RATINGS - HEALTH: 2 FLAMMABILITY: 3 REACTIVITY: 0

PREVIOUS MSDS REVISION DATE: 06/19/07

VOLATILE ORGANIC COMPOUNDS (VOCs): 4.74 lbs/gal, 568 grams/ltr

LEGEND: N.A. - Not Applicable, N.E. - Not Established,
N.D. - Not Determined

The information contained in this MSDS has been checked and should be accurate. However, it is the responsibility of the user to comply with all Federal, State, and Local laws and regulations.