
MATERIAL SAFETY DATA SHEET

=====|
 | SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION |
 =====|

PRODUCT NAME : GRAFFITI OUT
 IDENTIFICATION NUMBER: GWB10-FG DATE PRINTED: 02/03/10
 PRODUCT USE/CLASS :

SUPPLIER: Specialty Coatings & Chemicals Inc
 7360 Varna Ave.
 North Hollywood, CA 91605-4060
 Chemtrec: 1-800-424-9300
 24 Hour Emergency Hotline

MANUFACTURER: Specialty Coatings & Chemicals Inc
 7360 Varna Ave.
 North Hollywood, CA 91605-4060
 Chemtrec: 1-800-424-9300
 24 Hour Emergency Hotline

PREPARER: A.C.Macdonald, PHONE: 323-875-0233, PREPARE DATE: 02/03/10

=====|
 | SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS |
 =====|

ITEM	CHEMICAL NAME	CAS NUMBER	WT/WT % LESS THAN
01	N-PROPOXYPROPANOL	1569-01-3	55.0 %
02	2-BUTOXYETHANOL	111-76-2	50.0 %
03	DIETHYLENE GLYCOL N-BUTYL ETHER	112-34-5	5.0 %
04	Limonene	5989-27-5	5.0 %

ITEM	EXPOSURE LIMITS					
	ACGIH TLV-TWA	ACGIH TLV-STEL	OSHA PEL-TWA	OSHA PEL-CEILING	COMPANY TLV-TWA	SKIN
01	N.E.	N.E.	N.E.	N.E.	N.E.	YES
02	25 ppm	50 ppm*	25 ppm	50 ppm	N.E.	NO
03	N.E.	N.E.	N.E.	N.E.	N.E.	NO
04	N.E.	N.E.	N.E.	N.E.	N.E.	NO

(See Section 16 for abbreviation legend), * - Ceiling Value

=====|
 | SECTION 3 - HAZARDS IDENTIFICATION |
 =====|

*** EMERGENCY OVERVIEW ***: No Information.

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Severely irritating. If not removed promptly, will injure eye tissue, which may result in permanent damage.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Causes skin irritation. Allergic reactions are possible. Prolonged or repeated contact can result in

=====|
 | SECTION 3 - HAZARDS IDENTIFICATION |
 |=====|

defatting and drying of the skin which may result in skin irritation and dermatitis (rash). Harmful if inhaled, swallowed or absorbed through the skin.

EFFECTS OF OVEREXPOSURE - INHALATION: Prolonged inhalation may be harmful. Reports have associated repeated and prolonged occupational overexposure to solvents with brain and nervous system damage. Intentional misuse by inhaling the contents may be harmful.

EFFECTS OF OVEREXPOSURE - INGESTION: This product is not designed to be ingested; accordingly the user of this product must take appropriate safety measures to prevent ingestion.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: Overexposure may cause kidney damage. May cause liver disorder (e.g., edema, proteinuria) and damage. Overexposure may cause blood disorders.

PRIMARY ROUTE(S) OF ENTRY: SKIN CONTACT SKIN ABSORPTION INHALATION
 INGESTION EYE CONTACT

=====|
 | SECTION 4 - FIRST AID MEASURES |
 |=====|

FIRST AID - EYE CONTACT: Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

FIRST AID - SKIN CONTACT: Wash with soap and water. Get medical attention if irritation develops or persists.

FIRST AID - INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

FIRST AID - INGESTION: Get medical attention immediately. If swallowed, induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

=====|
 | SECTION 5 - FIRE FIGHTING MEASURES |
 |=====|

FLASH POINT: 210 F LOWER EXPLOSIVE LIMIT: 0.9 %
 (PENSKY-MARTENS C.C.) UPPER EXPLOSIVE LIMIT: 99.9 %

AUTOIGNITION TEMPERATURE:

EXTINGUISHING MEDIA: CO2 DRY CHEMICAL FOAM WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS: Vapors may form explosive mixture with air. Vapors can travel to a source of ignition and flash back. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR

SECTION 5 - FIRE FIGHTING MEASURES

EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner, or properly disposed of.

SPECIAL FIREFIGHTING PROCEDURES: Containers can build up pressure if exposed to heat (fire). As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. Water runoff can cause environmental damage. Dike and collect water used to fight fire.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Avoid runoff into storm sewers and ditches which lead to waterways. Wear a self-contained breathing apparatus and appropriate personal protective equipment. (See Exposure Controls/Personal Protection Section)

SECTION 7 - HANDLING AND STORAGE

HANDLING: This product is to be used for industrial or professional uses only and is to be applied only by those who are trained in its safe and proper application. When transferring material ground and bond containers and use spark proof tools and explosion proof equipment. Wash thoroughly after handling.

STORAGE: Keep away from heat, sparks and flame. Keep container closed when not in use.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Sufficient ventilation, in volume and pattern, should be provided to keep air contamination below current applicable OSHA permissible exposure limit or ACGHI's TLV limit. Good general ventilation should be sufficient to control airborne levels. Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product. Use explosion-proof ventilation equipment. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

RESPIRATORY PROTECTION: A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

any other circumstances where air purifying respirators may not provide adequate protection.

SKIN PROTECTION: Where contact is likely, wear chemical resistant gloves, a chemical suit, rubber boots, and chemical safety goggles plus a face shield. Use chemical splash goggles and face shield (ANSI Z87.1 or approved equivalent).

EYE PROTECTION: Wear safety glasses with side shields (or goggles) and a face shield.

OTHER PROTECTIVE EQUIPMENT: No Information.

HYGIENIC PRACTICES: Wash hands before eating. Follow all MSDS/label precautions even after container is emptied because they may retain product residues. Avoid contact with eyes, skin, and clothing.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

BOILING RANGE : 210 - 447 F VAPOR DENSITY : Is heavier than air
ODOR : Citrus ODOR THRESHOLD :
APPEARANCE : Clear liquid EVAPORATION RATE: Is slower than Ether
SOLUBILITY IN H2O : Miscible
FREEZE POINT : SPECIFIC GRAVITY: 0.9966
VAPOR PRESSURE : pH @ 0.0 % :
PHYSICAL STATE : VISCOSITY :
COEFFICIENT OF WATER/OIL DISTRIBUTION:

(See Section 16 for abbreviation legend)

SECTION 10 - STABILITY AND REACTIVITY

CONDITIONS TO AVOID: No Information.

INCOMPATIBILITY: No Information.

HAZARDOUS DECOMPOSITION PRODUCTS: No Information.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

SECTION 11 - TOXICOLOGICAL PROPERTIES

No product or component toxicological information is available.

=====
 | SECTION 12 - ECOLOGICAL INFORMATION |
 =====

ECOLOGICAL INFORMATION: No Information.

 =====
 | SECTION 13 - DISPOSAL CONSIDERATIONS |
 =====

DISPOSAL METHOD: Dispose in accordance with State, local and Federal regulations.

 =====
 | SECTION 14 - TRANSPORTATION INFORMATION |
 =====

No transportation information is available.

 =====
 | SECTION 15 - REGULATORY INFORMATION |
 =====

U.S. FEDERAL REGULATIONS: AS FOLLOWS -

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

CERCLA - SARA HAZARD CATEGORY:

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

FIRE HAZARD

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

CHEMICAL NAME	CAS NUMBER	WT/WT % IS LESS THAN
2-BUTOXYETHANOL	111-76-2	50.0 %
DIETHYLENE GLYCOL N-BUTYL ETHER	112-34-5	5.0 %

TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

CHEMICAL NAME	CAS NUMBER
No information is available.	

INTERNATIONAL REGULATIONS: AS FOLLOWS -

CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings.

CANADIAN WHMIS CLASS: No information available.

=====

SECTION 15 - REGULATORY INFORMATION

=====

GOVERNMENT REGULATIONS:: No Information.

=====

SECTION 16 - OTHER INFORMATION

=====

HMIS RATINGS - HEALTH: 2* FLAMMABILITY: 2 REACTIVITY: 0

PREVIOUS MSDS REVISION DATE: 01/15/10

VOLATILE ORGANIC COMPOUNDS (VOCs): 7.32 lbs/gal, 877 grams/ltr

LEGEND: N.A. - Not Applicable, N.E. - Not Established,
N.D. - Not Determined

=====