



Sailing Services stocks rope for most sailors from traditional yachts to the most high-tech race boats and everything in between. Our team has over 40 years of experience delivering top quality products around the world.

CONTACT US FOR PRICING

All the prices shown here are list prices by the foot. Sailing Services sells at discounted rates by the foot or full spool to the public as well as tradesmen and retailers.

Trade Pricing:

We welcome bona-fide trade customers and have a deep commitment to your success. Contact us to set up an account to receive trade pricing.

Splicing Services:

Sailing Services offers splicing for running rigging, dock lines, mooring lines and architectural installs.

For more information please contact us at (305) 758-1074 or sales@sailingservices.com.

Quantity Discounts

Cut Lengths:

Additional discounts may apply on large cut-length orders (sold by the foot). *Contact us for details.*

Full Spools:

Purchases of full spools carry a higher trade discount than cut-lengths. *Most spools are 600', but can vary by size and manufacturer. Contact us for details.*

Remnants:

Remnants are new rope, but sold in odd lengths. Usually from the ends of spools or bits leftover after making custom halyards or sheets. Remnants carry a much deeper discount than cut-length rope. Remnants cannot be cut and are sold at whatever length they may be. Contact us for details or for a list of currently available remnants.

www.sailingservices.com

Splicing Services

- Reeving Eyes
- Wire to Rope Splices
- Rope to Chain Splices
- High-Tech Splices
- Whipping Rope Ends
- 3 Strand Eye Splices
- Mega Braid Eye Splices
- Double Braid Eye Splices
- Single Braid Brummel Eye Splices





Splicing Labor Charges

These labor charges are **estimates** for use as a guide by professional riggers and their customers.

Splicing assumes the use of new product and normal construction. Used rope is generally not spliceable.

Some construction in double braid and single braid presents challenging problems due to tight braiding and irregular crossover between the core and the cover. **Quantity Discounts are Available, Contact Us for a Quote!**

Eye Splices - 3-Strand

Part No.	Description	Price
LAES3S08.....	1/4" 3-Strand Eye Splice	10.00
LAES3S10.....	5/16" 3-Strand Eye Splice	10.00
LAES3S12.....	3/8" 3-Strand Eye Splice	12.00
LAES3S14.....	7/16" 3-Strand Eye Splice	12.00
LAES3S16.....	1/2" 3-Strand Eye Splice	13.00
LAES3S18.....	9/16" 3-Strand Eye Splice	15.00
LAES3S20.....	5/8" 3-Strand Eye Splice	20.00
LAES3S24.....	3/4" 3-Strand Eye Splice	25.00
LAES3S32.....	1" 3-Strand Eye Splice.....	30.00

Eye Splices - Single Braid Brummel Splice

Part No.	Description	Price
LAESSBR04 ..	1/8" Brummel Splice, Interlocked Eye	7.50
LAESSBR06 ..	3/16" Brummel Splice, Interlocked Eye ...	10.00
LAESSBR08 ..	1/4" Brummel Splice, Interlocked Eye	10.00
LAESSBR10 ..	5/16" Brummel Splice, Interlocked Eye ...	12.00
LAESSBR12 ..	3/8" Brummel Splice, Interlocked Eye	12.00
LAESSBR14 ..	7/16" Brummel Splice, Interlocked Eye....	15.00
LAESSBR16 ..	1/2" Brummel Splice, Interlocked Eye	15.00
LAESSBR18 ..	9/16" Brummel Splice, Interlocked Eye	17.50
LAESSBR20 ..	5/8" Brummel Splice, Interlocked Eye	18.50
LAESSBR24 ..	3/4" Brummel Splice, Interlocked Eye	20.00
LAESSBR32 ..	1" Brummel Splice, Interlocked Eye.....	25.00

Eye Splices - Double Braid

Part No.	Description	Price
LAESDB08 ...	1/4" Double Braid Eye Splice	10.00
LAESDB10....	5/16" Double Braid Eye Splice	10.00
LAESDB12.....	3/8" Double Braid Eye Splice	13.00
LAESDB14....	7/16" Double Braid Eye Splice	13.00
LAESDB16....	1/2" Double Braid Eye Splice.....	16.00
LAESDB18....	9/16" Double Braid Eye Splice	18.00
LAESDB20....	5/8" Double Braid Eye Splice.....	20.00
LAESDB24....	3/4" Double Braid Eye Splice	25.00
LAESDB32....	1" Double Braid Eye Splice	35.00

Eye Splices - Mega Braid

Part No.	Description	Price
LAESMB20 ...	5/8" Mega Braid Eye Splice	40.00
LAESMB24 ...	3/4" Mega Braid Eye Splice	50.00
LAESMB32 ...	1" Mega Braid Eye Splice	60.00
LAESMB40 ...	1-1/4" Mega Braid Eye Splice.....	70.00
LAESMB48 ...	1-1/2" Mega Braid Eye Splice	80.00



Specialty Splices

Part No.	Description	Price
LAESPCC	Eye Splice Parallel Core (StaSet X)	35.00
LAEE.....	End-to-End Line Drive Splice.....	30.00

Wire to Rope Splice

Part No.	Description	Price
LATS04.....	Wire/Double Braid Splice to 1/8" Wire ...	35.00
LATS05.....	Wire/Double Braid Splice to 5/32" Wire .	40.00
LATS06.....	Wire/Double Braid Splice to 3/16" Wire..	45.00
LATS07.....	Wire/Double Braid Splice 7/32" Wire.....	60.00
LATS08.....	Wire/Double Braid Splice 1/4" Wire.....	65.00
LATS10.....	Wire/Double Braid Splice 5/16" Wire.....	80.00
LATS12.....	Wire/Double Braid Splice 3/8" Wire.....	130.00
LAWR12	Wire to Single Braid Splice.....	30.00

Rope to Chain Splices

Part No.	Description	Price
LACS*	3-Strand Rope to Chain.....	30.00
LACMP*	Mega Plait to Chain.....	70.00

*Rope to chain splice pricing may change depending on the size of the rope.

Hi-Tech Splices

Part No.	Description	Price
LAESE.....	Eye Splice Spect/Techn/Kev/Vec	35.00
LATB.....	Hi-Tech to Braid Splice	50.00
LASC	Stripped Cover	35.00

Finishing Touches for Rope

Part No.	Description	Price
LAWP	Whipping on Rope End	4.00
LAREV	Reeving Eye (not load bearing)	10.00



Rope for Racing: Double Braids

Endura Braid™



Endura Braid™ features a specially engineered 12-strand Dyneema® SK78 core, with Marine-Tech coating, and a 24-carrier braided polyester cover.

Endura Braid features a high strength-to-weight ratio, very low stretch, low creep, and outstanding durability. The coated braided core is color matched to the cover and ideal for durable tapered sheets and halyards.

Use for sheets, halyards, guys, topping lifts, reef lines, or low-stretch control lines.

Euro Style Colors



List Pricing

Part No.	Dia. Inches	Dia. MM	Tensile Lbs.	Weight Lbs/100'	White Price/ft	Solid Price/ft	Euro Price/ft
NEEND06*	3/16"	5mm	3,100	1.1	1.13	1.13	N/A
NEEND08*	1/4"	6mm	4,500	1.8	1.71	1.71	1.71
NEEND10*	5/16"	8mm	8,100	2.7	2.44	2.44	2.44
NEEND12*	3/8"	10mm	11,000	3.9	3.32	3.32	3.32
NEEND14*	7/16"	11mm	14,900	5.3	4.28	4.28	4.28
NEEND16*	1/2"	12mm	21,500	6.9	5.54	5.54	5.54
NEEND18*	9/16"	14mm	25,200	8.8	7.14	7.14	7.14
NEEND20*	5/8"	16mm	29,000	10.8	8.73		special order

*Add Color Code: BL (Solid Blue), G (Solid Green), R (Solid Red), W (White)

*Euro Colors: EUBK (Euro-Black), EUBL (Euro-Blue), EUG (Euro-Green), EUR (Euro-Red), EUW (Euro-White), EUY (Euro-Yellow).

*Requires Hi-Tech Eye Splice.



WarpSpeed II



High strength, low stretch, and very low weight make WarpSpeed II the high-performance racer's choice for double braid ropes. The strength member is 100% SK78 fiber. The cover is a flexible 24-strand polyester that provides good handling, excellent performance in stoppers and clutches, and enhanced abrasion resistance. The cover can be stripped when desired for greater weight savings.

Part No.	Dia. Inches	Dia. MM	Average Strength/Lbs.	Weight lbs/100'	List Price/ft
SAWII08*	1/4"	6mm	5,100	1.6	1.43
SAWII10*	5/16"	8mm	6,200	3.0	1.87
SAWII12*	3/8"	9mm	9,800	3.8	2.52
SAWII14*	7/16"	11mm	14,000	5.8	3.61
SAWII16*	1/2"	12mm	21,000	7.0	4.83
SAWII18*	9/16"	14mm	26,500	8.2	6.43

*Add Color Code: BK (Black), R (red), G (Green), BL (Blue)



ARC™



This cover only material combines the heat resistant fibers of Technora® and Nomex with colored polyester to improve abrasion resistance, and aids in line identification. When combined with a 12-Strand Dyneema core, the ARC cover helps to prevent surface melting and surging when the line is released under very high loads. ARC™ is ideal for runner tails, as well as mainsheets and genoa sheets. Stocked in 10mm. 8mm available in black only.

Part No.	Dia. Inches	Dia. MM	Weight lbs/100'	List Price/ft
NEARCM08PBKF	5/16"	8mm	3.7	2.30
NEARCM10P*	3/8"	10mm	6.2	3.55

*Add Color Code: BKF (Black Fleck), GF (Green Fleck), RF (Red Fleck).



Poly Tec



Poly Tec uses the same high-strength low-weight Dyneema® core as Endura Braid while adding an extra durable cover made from a blend of Technora and Polyester fibers. Poly Tec offers excellent abrasion and cut resistance, heat dissipation, and a level of grip that other high performance ropes don't offer. Use for applications that require a low stretch, low creep, and extra-grippy line such as halyards, sheets and control lines.

Part No.	Dia. Inches	Dia. MM	Tensile Lbs.	Weight lbs/100'	List Price/ft
NEPT75M06	1/4"	6	3.0	5590	2.46
NEPT75M08	5/16"	8	4.4	8840	3.65

*Add Color Code: BL (Blue), O (Orange), R (Red), G (Green), Y (Yellow)





Nexus Pro



The latest innovation from New England Ropes, Nexus Pro has been developed to be the gold standard for performance-minded sailors. Nexus Pro has a durable, lightweight cover that offers excellent grip and holding power. The core is pure Dyneema for ultra-strength and low-stretch. Designed for today's newest one-design sheets and control lines. Perfect for boats that require high tensile such as J70, Etchells, Melges, J24, and larger one-designs.

Part No.	Dia. Inches	Dia. MM	Tensile Lbs.	Weight Lbs./100'	List Price/ft
NENXPM06*	1/4"	6mm	3,600	1.15	1.45
NENXPM07*	9/32"	7mm	6,000	1.75	1.71
NENXPM08*	5/16"	8mm	7,300	2.40	2.27
NENXPM10*	3/8"	10mm	11,000	3.40	2.93

*Add Color Code: BK (Black Fleck), BF(Blue Fleck), RF (Red Fleck)



Ultra-Lite



Designed specifically for light air spinnaker and jib sheets, control lines, and halyards. Ultra-Lite is constructed with a polypropylene cover and composite core of polypropylene and Dyneema®. It is lighter than 100% polyester double braids. Sailors will realize up to 26% weight savings with the same breaking strength and less stretch.

Part No.	Dia. Inches	Dia. MM	Average Strength/Lbs.	Weight Lbs./100'	List Price/ft
SAUL06*	3/16"	5mm	1,200	0.9	0.48
SAUL08*	1/4"	6mm	2,200	1.9	0.77
SAUL10*	5/16"	8mm	2,900	2.5	1.01
SAUL12*	3/8"	10mm	4,400	3.2	1.45

*Add Color Code: G (Green), BK (Black), R (Red), BL (Blue)



MGP Furler Line



MGP Furler 50 from Marlow is a structural cover over a nonstructural core. The cover is made from a Vectran / Technora cover giving it superior heat and abrasion resistance. The snakeskin pattern allows for easy end-to-end splicing with no diameter increase.

Part No.	Dia. Inches	Dia. MM	Tensile Lbs.	Weight Lbs./100'	List Price/Ft.
MARMGPM06BK	6				1.69
MARMGPM08BK	8				2.04
MARMGPM10BK	10				3.40



Rope for Racing: 12-Strand Single Braids

HSR-75




With STS HSR, sailors have the option to use a rope with a smaller diameter without losing (and in most cases gaining) tensile strength. In addition, the ability to use smaller rope diameters without compromising on strength also reduces the overall weight of the line.

Part No.	Dia. Inches	Dia. MM	Average Strength/Lbs.	Weight Lbs./100'	List Price/ft
NESTS-HSRM03	1/8"	3mm	5,200	0.6	0.96
NESTS-HSRM05	3/16"	5mm	9,475	1.3	2.06
NESTS-HSRM06	1/4"	6mm	12,385	1.7	2.92
NESTS-HSRM07	9/32"	7mm	18,700	2.5	3.56
NESTS-HSRM08	5/16"	8mm	23,600	3.3	4.95
NESTS-HSRM09		9mm	25,300	4.5	5.92
NESTS-HSRM11	7/16"	11mm	31,530	5.1	10.35
NESTS-HSRM12	1/2"	12mm	43,675	6.80	10.79

*Only available in silver



Amsteel Blue



AmSteel®Blue - is a torque-free, 12-strand single braid that yields the maximum in strength-to-weight ratio and, size-for-size, is the same strength as steel, yet it floats. An excellent wire rope replacement with extremely low stretch and superior flex fatigue and wear resistance. It is specially designed for improved service life in applications where creep results from long-term static loads.

Part No.	Dia. Inches	Dia. MM	Tensile Lbs.	Weight Lbs./100'	List Price/ft
SAAS78764*	7/64"	2.5mm	1,600	0.30	0.29
SAAS7804*	1/8"	3mm	2,500	0.50	0.46
SAAS7805*	5/32"	4mm	4,000	0.75	0.76
SAAS7806*	3/16"	5mm	5,400	0.75	0.93
SAAS7808*	1/4"	6mm	8,600	1.00	1.46
SAAS7810*	5/16"	8mm	13,700	1.60	2.42
SAAS7812*	3/8"	9mm	19,600	2.70	3.40
SAAS7814*	7/16"	11mm	23,900	4.50	3.86
SAAS7816*	1/2"	12mm	34,000	5.90	5.53
SAAS7820*	5/8"	16mm	52,800	10.20	9.18


*Add Color Code: BK (Black, BL (Blue), GY (Gray)





Rope for Performance Cruisers

VPC™



New England Ropes VPC™ is a unique mid-tech product for sheets and halyards. It features a strong core of blended Vectran™ and polyolefin with a durable polyester cover. VPC™ was designed to fill the gap between polyester lines and ultra high performance racing lines. Intended for the casual racer and offshore cruiser, VPC™ will result in noticeable performance improvements when used for mainsheets, halyards, or jib sheets.

Part No.	Dia. Inches	Dia. MM	Tensile Lbs.	Weight Lbs./100'	List Price/ft
NEVPC10*	5/16"	8mm	5,500	3.3	1.28
NEVPC12*	3/8"	10mm	6,500	3.9	1.68
NEVPC14*	7/16"	11mm	8,500	5.9	2.17
NEVPC16*	1/2"	12mm	10,200	6.4	2.70

*Add Color Code: W (White), BLF (Blue Fleck), GF (Green Fleck), RF (Red Fleck)



MLX



MLX is a lightweight, core-dependent line that has excellent strength and low stretch. The core is Samthane coated to match the cover, making the line strippable for greater weight savings. Use for control lines, halyards, jib/genoa sheets, mainsheets, spinnaker sheets. SK 65 Core.

Part No.	Diameter Inches	Diameter MM	Avg. Strength Lbs.	Weight Lbs./100'	List Price/ft
SAMLX10*	5/16"	8mm	6,900	3.0	1.56
SAMLX12*	3/8"	10mm	8,700	3.8	1.97
SAMLX14*	7/16"	11mm	12,200	5.8	2.83
SAMLX16*	1/2"	12mm	14,000	8.2	3.92

*Add Color Code: W (White), BLF (Blue Fleck), GF (Green Fleck), RF (Red Fleck)



Sta-Set™



Sta-Set™ is the #1 polyester double braid in America and is a strong, flexible, and long wearing line. Sta-Set™ has high strength, low stretch, and is extremely durable, yet remains soft over time. A true multi-purpose line used for sheets, halyards and control lines on a wide variety of boats.

Solid colors have white fleck, as shown on left.

Part No.	Dia. Inches	Dia. MM	Tensile Lbs.	Weight Lbs./100'	List Pricing		
					White Price/ft	Fleck Price/ft	Solid Price/ft
NESS06*	3/16"	5mm	1,400	1.1	0.39	0.41	0.45
NESS08*	1/4"	6mm	2,350	2.0	0.59	0.62	0.65
NESS10*	5/16"	8mm	3,850	3.1	0.77	0.80	0.89
NESS12*	3/8"	10mm	5,100	4.3	0.99	1.04	1.12
NESS14*	7/16"	11mm	7,000	6.0	1.28	1.34	1.46
NESS16*	1/2"	12mm	10,100	7.8	1.60	1.68	1.81
NESS18*	9/16"	14mm	11,700	10.1	2.06	2.16	2.35
NESS20*	5/8"	16mm	16,900	11.9	2.42	2.54	2.76
NESS24**	3/4"	18mm	23,500	17.0	3.01		

*Add Color Code: W (White), BLF (Blue Fleck), GF (Green Fleck), RF (Red Fleck), BL (Blue), G (Green), R (Red), BK (Black)
**Available in white only.



Sta-Set X™



Sta-Set X™ is the strongest lowest stretch polyester line available with a patented parallel fiber core and a braided cover made from a blend of spun and filament polyester.

Use for halyards, spinnakers and guys on cruising boats.

Part No.	Dia. Inches	Dia. MM	Tensile Lbs.	Weight Lbs./100'	List Price/ft
NESSX12W	3/8"	10mm	5,300	4.5	1.02
NESSX14W	7/16"	11mm	7,700	6.1	1.32
NESSX16W	1/2"	12mm	9,700	8.4	1.71



Regatta Braid™




Flexible and easy to handle. A 12-strand single braid made of spun and filament polyester. A soft and supple, easy-to-handle line that runs freely and does not kink. Ideal for mainsheets and furling lines on cruisers and club racers. White with red tracer only.

Part No.	Dia. Inches	Dia. MM	Tensile Lbs.	Weight Lbs./100'	List Price/ft
NEREG08	1/4"	6mm	2,550	2.2	0.48
NEREG10	5/16"	8mm	3,300	3.0	0.67
NEREG12	3/8"	10mm	4,800	4.0	0.90
NEREG14	7/16"	11mm	6,500	6.3	1.11
NEREG16	1/2"	12mm	8,000	7.0	1.57
NEREG20	5/8"	16mm	12,400	10.3	1.99



T900™



T900™ has a polyester cover and a blended core of Dyneema® SK75 and Technora® for a combination of low weight plus low creep in a durable, affordable package. An excellent choice for static loads such as halyards and guys.

Part No.	Dia. Inches	Dia. MM	Tensile Lbs.	Weight Lbs./100'	List Price/ft
NET90010*	5/16"	8mm	6,800	3.2	2.17
NET90012*	3/8"	10mm	11,000	5.1	3.10
NET90014*	7/16"	11mm	14,300	5.5	3.67
NET90016*	1/2"	12mm	15,700	6.4	4.54
NET90018*	9/16"	14mm	21,750	8.8	5.88

*Add Color Code: W (White), BLF (Blue Fleck), GF (Green Fleck), RF (Red Fleck)





Regatta Lite™




A 12-strand, single braid, multi-filament polypropylene line. Extremely lightweight (wet or dry). Does not kink and is easy to handle.

Part No.	Dia. Inches	Dia. MM	Tensile Lbs.	Weight Lbs./100'	List Price/Ft
NEREGL08P	1/4"	6mm	1,050	1.3	0.39
NEREGL10P	5/16"	8mm	2,560	2.2	0.56
NEREGL12P	3/8"	10mm	3,200	2.9	0.70



Bzzz Line™



Single braid construction makes Bzzz™ line kink-free, while the combination of spun polyester and multi-filament polypropylene make it soft, easy to grip, and lightweight.

Part No.	Dia. Inches	Dia. MM	Tensile Lbs.	Weight Lbs./100'	List Price/Ft
NEBZ09*	9/32"	7mm	1,730	1.9	0.65
NEBZ10*	5/16"	8mm	3,000	2.5	0.77

*Add Color Code: BL (Blue), GD (Gold), GY (Grey), Y (Yellow)



Finish Line™



The strongest pre-stretch line on the market, Finish Line is made from high-tenacity tension-set polyester with an 8-strand "nubby" cover and continuous filament core. It is excellent as a dinghy control line; has a strong, durable cover, yet is comfortable on the hand, flexible, and easy to knot.

Part No.	Dia. Inches	Dia. MM	Tensile Lbs.	Weight Lbs./100'	List Price/Ft
NEFL05*	5/32"	4mm	920	0.8	0.44
NEFL06*	3/16"	5mm	1,550	1.3	0.57
NEFL08*	1/4"	6mm	2,100	1.7	0.75

*Add Color Code: GY (Grey), R (Red), W (White)



Spyderline™




Excellent for lightweight control line, and for all small diameter, high load applications. Spyder Line is constructed with a Dyneema® SK-75 core and a smooth, twill pattern polyester cover. Flexible, yet firm enough to be fed through small leads, micro blocks, and purchase systems.

Part No.	Dia. Inches	Dia. MM	Tensile Lbs.	Weight Lbs./100'	List Price/Ft
NESL02*	1/16"	2mm	350	0.2	0.26
NESL04*	1/8"	3mm	1,250	0.5	0.59
NESL05*	5/32"	4mm	1,860	0.9	0.87
NESL06*	3/16"	5mm	3,000	1.4	1.26

*Add Color Code: BK (Black), LM (Lime), MG (Mango), P (Purple), R (Red)



Salsa Line™



A high-tech version of classic Regatta Braid. Exceptionally strong yet soft single braid, constructed with a blend of Dyneema® SK-75 plus spun and filament polyester. Salsa Line is easy to grip and has proven to be a great kink-free sheet for larger dinghies and keelboats.

Part No.	Dia. Inches	Dia. MM	Tensile Lbs.	Weight lbs/100'	List Price/Ft
NESAL08*	1/4"	6mm	2,850	1.8	1.28
NESAL10*	5/16"	8mm	4,000	3.0	1.51
NESAL12*	3/8"	10mm	5,000	3.5	2.10

*Add Color Code: G (Green), GY (Grey), R (Red)



Dinghy Tow Rope



Dinghy Tow Rope is a durable colored and spliceable tow line that floats on the surface fo the water for improved visibility.

Part No.	Dia. Inches	Dia. MM	Tensile Lbs.	Weight lbs/100'	List Price/Ft
NETOW14RF	7/16"	11mm	5,050	5.3	1.00





Rope for Anchor & Docking

Premium 3-Strand Nylon

Premium 3-strand filament nylon. Highest strength and elongation. Ideal for uses requiring high energy absorption.



The combination of premium-grade nylon, four-stage construction, and a special marine coating results in improved handling, greater chafe resistance, minimal hardening and longer life. Good UV resistance.

Part No.	Dia.		Tensile Lbs.	Weight Lbs./100'	List Pricing	
	Inches	MM			White Price/ft	Black Price/ft
NEN308*	1/4"	6mm	2,100	1.6	0.26	0.32
NEN310*	5/16"	8mm	3,000	2.4	0.38	0.50
NEN312*	3/8"	10mm	4,250	3.5	0.49	0.65
NEN314*	7/16"	11mm	6,000	4.6	0.68	0.92
NEN316*	1/2"	12mm	7,500	6.3	0.85	1.14
NEN318*	9/16"	14mm	8,800	8.0	1.10	1.47
NEN320*	5/8"	16mm	11,650	9.6	1.34	1.81
NEN324*	3/4"	18mm	17,150	13.7	1.88	2.53
NEN328*	7/8"	22mm	22,300	18.0	2.53	3.41
NEN332*	1"	25mm	27,700	24.3	3.33	4.49

*Add Color Code: W (White), B (Black)



Double Braid Nylon

Double Braid Nylon - Nylon Cover/Nylon Core. Conforms to MIL-R-24050 B&C. High grade marine nylon with special torque-balanced construction.



Elastic double braid construction has excellent energy absorbing characteristics. Controlled elongation and excellent abrasion resistance, wet or dry. Minimal strength loss due to UV.

Part No.	Dia.		Tensile Lbs.	Weight Lbs./100'	List Pricing	
	Inches	MM			White Price/ft	Solid Price/ft
NENB12*	3/8"	9mm	4,900	3.6	0.79	0.97
NENB16*	1/2"	12mm	8,500	6.3	1.25	1.48
NENB20*	5/8"	16mm	13,500	10.0	1.84	2.26
NENB24*	3/4"	18mm	19,400	14.3	2.53	3.06
NENB28*	7/8"	22mm	26,300	19.4	3.32	3.96
NENB32*	1"	25mm	34,000	25.4	4.17	5.05
NENB40*	1-1/4"	30mm	52,000	40.0	6.54	7.70

*Add Color Code: W (White), BK (Black), BL (Blue)

**Other colors available for Special Order



Mega Braid™

Mega Braid's unique 12-strand, single braid construction offers a combination of good looks, ease of handling, strength, and controlled elongation. Ideal for dock and anchor lines for yachts over 40'.



Part No.	Dia.		Tensile Lbs.	Weight Lbs./100'	List Pricing	
	Inches	MM			White Price/ft	Black Price/ft
NEMB20*	5/8"	16mm	10,300	10.4	1.95	2.35
NEMB24*	3/4"	18mm	13,400	15.0	2.53	3.04
NEMB28*	7/8"	22mm	21,100	19.3	3.22	3.86
NEMB32*	1"	25mm	24,900	23.0	4.00	4.81
NEMB36*	1-1/8"	28mm	34,900	31.0	5.02	6.02
NEMB40*	1-1/4"	30mm	41,000	36.0	5.58	6.95
NEMB48*	1-1/2"	36mm	48,000	55.5	8.81	10.05

*Add Color Code: W (White), B (Black)



Mega Braid II™

Each of Mega Braid II's 12 strands are individually braided resulting in a firm yet flexible rope that resists snags and chafing. Excellent abrasion resistance and easy to coil. Ideal for anchor and dock lines for boats over 45'.



Part No.	Dia.		Tensile Lbs.	Weight Lbs./100'	List Pricing	
	Inches	MM			White Price/ft	Black Price/ft
NEMBII16*	1/2"	12mm	6,500	6.2	1.31	1.57
NEMBII18*	9/16"	14mm	8,500	7.3	1.65	1.96
NEMBII20*	5/8"	16mm	10,000	9.8	2.05	2.48

*Add Color Code: W (White), B (Black)



Mega Plait™

Mega Plait strikes a balance between a supple, firm, and easy handling line that can be used in mechanical windlasses without abrading or fraying. It features a tandem braid design for a "cube" shaped rope that works well in powered windlasses. White only.



Part No.	Dia.		Tensile Lbs.	Weight Lbs./100'	List Price/Ft
	Inches	MM			
NEMP16W	1/2"	12mm	7,500	6.0	1.35
NEMP20W	5/8"	16mm	10,000	10.4	2.14



Note

Rope diameters can vary depending on the type of rope and the manufacturer. Diameters, tensile or average strength, and weights are supplied by the manufacturers. For full details and specifications on a particular rope, please see the manufacturer's website.



Classic™



3-Strand Filament Polyester. Traditional low stretch running rigging. A continuous filament three strand polyester rope. Excellent abrasion resistance with low stretch and high strength. Used for halyards and control lines on dinghies and traditional boats. Easy to splice.

Part No.	Dia. Inches	Dia. MM	Tensile Lbs.	Weight Lbs./100'	List Price/Ft
NEPE3F06	3/16"	5mm	1,090	1.1	0.22
NEPE3F08	1/4"	6mm	2,150	2.0	0.34
NEPE3F10	5/16"	8mm	2,650	2.9	0.46
NEPE3F12	3/8"	10mm	4,400	4.8	0.65
NEPE3F14	7/16"	11mm	5,700	5.9	0.90
NEPE3F16	1/2"	12mm	7,500	7.9	1.08



Spun Classic™



3-Strand Spun Polyester. For a Traditional Look and Feel. A conventional three strand spun polyester rope. A soft (fuzzy), free running rope that resists jamming and kinking. Used on classic boats and dinghies for halyards, sheets and control lines. Also used as sailmakers' bolt rope.

Part No.	Dia. Inches	Dia. MM	Tensile Lbs.	Weight Lbs./100'	List Price/Ft
NEPE3S06	3/16"	5mm	1,200	1.4	0.22
NEPE3S08	1/4"	6mm	1,330	1.9	0.32
NEPE3S10	5/16"	8mm	2,000	2.7	0.45
NEPE3S12	3/8"	10mm	2,650	3.6	0.63
NEPE3S14	7/16"	11mm	3,250	4.8	0.88
NEPE3S16	1/2"	12mm	4,700	6	1.05



Lash It™



Small diameter Dynema® line for general purposes. Lash It™ is light weight, low stretch and extremely durable. Color: Grey. Sold by the spool only.

Part No.	Dia. Inches	Dia. MM	Avg Strength	Spool Length/Ft.	List Price/Ft
SALASH02-180	.1/16"	1.75mm	500 lbs	180'	36.67
SALASH02-600	.1/16"	1.75mm	500 lbs	600'	122.23
SALASH03-180	.3/32"	2.2mm	650lbs	180'	42.13
SALASH03-600	.3/32"	2.2mm	650lbs	600'	140.43



T-100™



T-100™ is made with a 100% Technora® fiber core and a braided polyester cover. Very low stretch. Perfect for light-air spinnaker sheets, tie-downs, and leech lines.

Part No.	Dia. Inches	Dia. MM	Tensile Lbs.	Spool Length/Ft.	List Price/Ft
NET10003	3/32"	2mm	950	1,500	0.44
NET10004	1/8"	3mm	1,280	1,200	0.47
NET10005	5/32"	4mm	2,300	900	0.59



Braided Polyester Cord



New England Rope's braided polyester cord is the perfect all-purpose cord. Made with a continuous filament polyester core covered in a polyester jacket. For general purpose use, such as flag halyards and tie-downs.

Part No.	Dia. Inches	Dia. MM	Tensile Lbs.	White Price/Ft.	Black Price/Ft.
NEDAC03	3/32"	2mm	350	0.07	0.08
NEDAC04	1/8"	3mm	530	0.09	0.10
NEDAC05	5/32"	4mm	730	0.15	0.17
NEDAC06	3/16"	5mm	1,000	0.16	0.19

*Add Color Code : W (White), BK (Black)



Messenger Line

Inexpensive single braid polyester line used for halyard messengers.

Part No.	Dia. Inches	Dia. MM	Spool Length (Ft.)	List Price/Ft
NEMSGR03*	3/32"	2mm	3,000	0.07

*Add Color Code: BK (Black), BL (Blue), GR (Green), R (Red)

Shock Cord

Filament rubber strands covered with a tight black polyester cover with excellent stretch and recover for long term use. Resistant to cracks, splits and breakage.

Part No.	Dia. Inches	Dia. MM	Spool Length (Ft.)	List Price/Ft
SHP04BK-SE	1/8"	3mm	100	0.18
SHP06BK-SE	3/16"	5mm	100	0.22
SHP08BK-SE	1/4"	6mm	100	0.40
SHP10BK-SE	5/16"	8mm	100	0.44
SHP12BK-SE	3/8"	10mm	100	0.57