

# SAFETY DATA SHEET

---

## SECTION 1) CHEMICAL PRODUCT AND SUPPLIER'S IDENTIFICATION

---

**Product ID:** 0940-XXXX-0010  
**Product Name:** MARKER, FELT SERIES II - ALL COLORS  
**Revision Date:** Feb 14, 2018 **Date Printed:** Feb 14, 2018  
**Version:** 1.0 **Supersedes Date:** N.A.  
**Manufacturer's Name:** TOUCH-UP SOLUTIONS  
**Address:** 4372 Providence Mill Rd Maiden, NC, US, 28650  
**Emergency Phone:** 1-800-535-5053 | International : 1-352-323-3500  
**Information Phone Number:** 1-828-428-9094  
**Fax:** 1-828-428-9970  
**Product/Recommended Uses:** Touch up and repair

---

## SECTION 2) HAZARDS IDENTIFICATION

---

### Classification

Eye Irritation - Category 2A  
Flammable Liquids - Category 1  
Skin Irritation - Category 2

### Pictograms



### Signal Word

Danger

### Hazardous Statements - Physical

Extremely flammable liquid and vapor

### Hazardous Statements - Health

Causes serious eye irritation  
Causes skin irritation

### Precautionary Statements - General

If medical advice is needed, have product container or label at hand.  
Keep out of reach of children.  
Read label before use.

### Precautionary Statements - Prevention

Wash with water and soap thoroughly after handling.  
Wear protective gloves/protective clothing/eye protection/face protection.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Keep container tightly closed.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ventilating/lighting equipment.  
Use only non-sparking tools.

Take action to prevent static discharges.

### Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

In case of fire: Use DRY chemical, alcohol-resistant foam, carbon-dioxide, water spray/fog to extinguish.

IF ON SKIN: Wash with plenty of water.

Specific treatment (see First-aid on this label).

If skin irritation occurs: Get medical advice/attention.

Take off contaminated clothing. And wash it before reuse.

### Precautionary Statements - Storage

Store in a well-ventilated place. Keep cool.

### Precautionary Statements - Disposal

Dispose of contents/container to disposal recycling center.

Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

**Acute toxicity of 14.12% of the mixture is unknown**

---

## SECTION 3) COMPOSITION, INFORMATION ON INGREDIENTS

---

CAS	Chemical Name	% By Weight
0000064-17-5	ETHYL ALCOHOL	31% - 51%
0000078-93-3	METHYL ETHYL KETONE	24% - 39%
NA-Proprietary	PolyKetone Resin	8% - 20%
0000067-63-0	ISOPROPYL ALCOHOL	4% - 9%
0000141-78-6	ETHYL ACETATE	0.2% - 3%
0007440-48-4	COBALT	0.1% - 1.7%
0000109-60-4	N-PROPYL ACETATE	0.1% - 0.9%

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

---

## SECTION 4) FIRST-AID MEASURES

---

### Eye Contact

Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for a duration of 15-20 minutes. Take care not to rinse contaminated water into the unaffected eye or onto the face. If eye irritation persists: Get medical advice/attention.

### Skin Contact

Take off contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Rinse skin with lukewarm, gently flowing water for a duration of 15-20 minutes. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before re-use.

### Ingestion

Rinse mouth. If unwell or concerned: Get medical attention/advice. Do NOT induce vomiting unless advised by Poison center or doctor.

### Inhalation

Remove source of exposure or move person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor, if you feel unwell.

---

## SECTION 5) FIRE-FIGHTING MEASURES

---

### Unsuitable Extinguishing Media

Do not use water jet.

### Special hazards in case of fire

Hazardous Combustion Products: Oxides of carbon.

Flammable components of this material may be lighter than water and burn while floating on the surface.

Vapors are heavier than air and may travel to a source of ignition and flash back.

### Special Protective Actions

Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear.

### Suitable Extinguishing Media

Dry chemical, foam, carbon dioxide is recommended. Water spray is recommended to cool or protect exposed materials or structures. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.

### Fire-Fighting Procedures

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Water may be ineffective but can be used to cool containers exposed to heat or flame. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid.

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

---

## SECTION 6) ACCIDENTAL RELEASE MEASURES

---

### Emergency Procedure

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

Isolate hazard area and keep unnecessary people away. Remove all possible sources of ignition in the surrounding area. Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.

Do not touch or walk through spilled material.

If spilled material is cleaned up using a regulated solvent, the resulting waste mixture may be regulated.

### Personal Precautions

Avoid breathing vapor. Avoid contact with skin, eye or clothing. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

### Environmental Precautions

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers.

### Methods and Materials for Containment and Cleaning Up

Cover spills with suitable inert absorbent like granulated clay and place in sealed chemical waste containers.

### Recommended Equipment

Positive pressure, full-face piece self-contained breathing apparatus (SCBA), or positive pressure supplied air respirator with escape SCBA (NIOSH approved).

---

## SECTION 7) HANDLING AND STORAGE

---

### General

Wash hands after use.

Do not get in eyes, on skin or on clothing.

Do not breathe vapors or mists.

Use good personal hygiene practices.

Eating, drinking and smoking in work areas is prohibited.

Remove contaminated clothing and protective equipment before entering eating areas.

Eyewash stations and showers should be available in areas where this material is used and stored.

### Ventilation Requirements

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source.

### Storage Room Requirements

Keep container(s) tightly closed and properly labeled. Store in cool, dry, well-ventilated areas away from heat, direct sunlight, strong

oxidizers and any incompatibilities. Store in approved containers and protect against physical damage. Keep containers securely sealed when not in use. Indoor storage should meet OSHA standards and appropriate fire codes. Containers that have been opened must be carefully resealed to prevent leakage. Empty containers retain residue and may be dangerous. Use non-sparking ventilation systems, approved explosion-proof equipment and intrinsically safe electrical systems in areas where this product is used and stored.

Do not cut, drill, grind, weld or perform similar operations on or near containers. Do not expose containers to heat, sparks, flame or other sources of ignition.

Ground and bond containers when transferring materials. Use procedures that prevent static electrical sparks. Static electricity may accumulate and create a fire hazard.

Use non-sparking ventilation systems, approved explosion-proof equipment and intrinsically safe electrical systems in areas where this product is used and stored.

## SECTION 8) EXPOSURE CONTROLS, PERSONAL PROTECTION

### Eye Protection

Wear eye protection with side shields or goggles. Wear indirect-vent, impact and splash resistant goggles when working with liquids. If additional protection is needed for entire face, use in combination with a face shield.

### Skin Protection

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Use of an apron and over-boots of chemically impervious materials such as neoprene or nitrile rubber is recommended to avoid skin sensitization. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Launder soiled clothes or properly disposed of contaminated material, which cannot be decontaminated.

### Respiratory Protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed. Check with respiratory protective equipment suppliers.

### Appropriate Engineering Controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

Chemical Name	OSHA TWA (mg/m3)	OSHA TWA (ppm)	OSHA STEL (mg/m3)	OSHA STEL (ppm)	OSHA Tables (Z1, Z2, Z3)	OSHA Carcinogen	OSHA Skin designation	NIOSH TWA (mg/m3)	NIOSH TWA (ppm)	NIOSH STEL (mg/m3)	NIOSH STEL (ppm)	NIOSH Carcinogen
COBALT	0.1				1			0.05				
ETHYL ACETATE	1400	400			1			1400	400			
ETHYL ALCOHOL	1900	1000			1			1900	1000			
ISOPROPYL ALCOHOL	980	400			1			980	400	1225	500	
METHYL ETHYL KETONE	590	200			1			590	200	885	300	
N-PROPYL ACETATE	840	200			1			840	200	1050	250	

Chemical Name	ACGIH TWA (mg/m3)	ACGIH TWA (ppm)	ACGIH STEL (mg/m3)	ACGIH STEL (ppm)	ACGIH Carcinogen	ACGIH TLV Basis	ACGIH Notations
COBALT	0.005(T)				A2	pneumonitis	RSEN;A2
ETHYL ACETATE	1440	400				URT & eye irr	
ETHYL ALCOHOL				1000	A3	URT irr	A3
ISOPROPYL ALCOHOL		200		400	A4	Eye & URT irr; CNS impair	A4;BEI
METHYL ETHYL KETONE	590	200	885	300		URT irr; CNS & PNS impair	BEI
N-PROPYL ACETATE	835	200	1040	250		Eye & URT	

(C) - Ceiling limit, A2 - Suspected Human Carcinogen, A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans, A4 - Not Classifiable as a Human Carcinogen, BEI - Substances for which there is a Biological Exposure Index or Indices, CNS - Central nervous system, impair - Impairment, irr - Irritation, PNS - Peripheral nervous system, URT - Upper respiratory tract

---

## SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

---

### Physical and Chemical Properties

VOC Regulatory(lb/gal)	1.26 lb/gal
Density	1.32 lb/gal
% Solids By Weight	14.12%
Specific Gravity	0.16
% VOC	95.74%
Density VOC	1.26 lb/gal
lb VOC/lb Solid	6.78 lb/lb
% HAPS	0.00%
Density HAPS	0.00 lb/gal
lb HAPS/lb Solid	0.00 lb/lb
lb HAPS/gal Solid	lb/gal
% VHAPS	0.00%
Density VHAPS	0.00 lb/gal
lb VHAPS/lb Solid	0.00 lb/lb

---

Appearance	Liquid
Odor Description	N/A
Odor Threshold	N/A
pH	N/A
Flammability	Flash point below 73°F/23°C
Flash Point Symbol	<
Flash Point	15.6 °C
Lower Explosion Level	N/A
Upper Explosion Level	N/A
Water Solubility	N/A
Coefficient Water/Oil	N/A
Vapor Density	N/A
Vapor Pressure	N/A
Low Boiling Point	N/A
High Boiling Point	N/A
Melting Point	N/A
Freezing Point	N/A
Viscosity	N/A
Evaporation Rate	N/A
Decomposition Pt	N/A
Auto Ignition Temp	N/A

---

## SECTION 10) STABILITY AND REACTIVITY

---

### Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

**Conditions to avoid**

Avoid flame, spark, heat, contact with air/water, visible light and contact with incompatible materials.

**Stability**

Stable in normal conditions

**Incompatible Materials**

Strong oxidizing agents, acids, alkalies, amines and water.

**Hazardous reactions/polymerization**

Will not occur.

---

**SECTION 11) TOXICOLOGICAL INFORMATION**

---

**Skin Corrosion/Irritation**

Causes skin irritation

**Serious Eye Damage/Irritation**

Causes serious eye irritation

**Carcinogenicity**

No Data Available

**Germ Cell Mutagenicity**

No Data Available

**Reproductive Toxicity**

No Data Available

**Respiratory/Skin Sensitization**

No Data Available

**Specific Target Organ Toxicity - Single Exposure**

No Data Available

**Specific Target Organ Toxicity - Repeated Exposure**

No Data Available

**Aspiration Hazard**

No Data Available

**Acute Toxicity**

No Data Available

**Potential Health Effects - Miscellaneous**

0000064-17-5 ETHYL ALCOHOL

The following medical conditions may be aggravated by exposure: liver disease. Tests in some laboratory animals indicate this compound may have embryotoxic activity. Tests in animals demonstrate reproductive toxicity. Ingestion may cause any of the following: stupor (central nervous system depression), gastrointestinal irritation. If absorbed through the skin, may be: harmful.

0000067-63-0 ISOPROPYL ALCOHOL

The following medical conditions may be aggravated by exposure: dermatitis, respiratory disease. Developmental toxicity was seen in rat's offspring at doses that were maternally toxic. Contact will cause moderate to severe redness and swelling, itching, tingling sensation, painful burning. May cause injury to the cornea of the eyes. Prolonged or repeated exposure may cause damage to any of the following organs/systems: liver. Ingestion studies on laboratory animals showed that very high oral doses caused increased liver and kidney weights.

0000078-93-3 METHYL ETHYL KETONE

Material is irritating to mucous membranes and upper respiratory tract. Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: central nervous system, eyes, respiratory system, skin. Prolonged or repeated overexposure may cause any of the following: conjunctivitis, dermatitis. High concentrations have caused embryotoxic effects in laboratory animals. Aspiration may occur during swallowing or vomiting, resulting in lung damage. Ingestion may cause headache, nausea, vomiting, dizziness, and drowsiness.

0000141-78-6 ETHYL ACETATE

Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: eyes, respiratory system, skin. Tests in laboratory animals have shown effects on any of the following organs/systems: blood, kidneys, liver.

0000064-17-5 ETHYL ALCOHOL

LC50 (mouse): Approximately 21000 ppm (4-hour exposure); cited as 39 g/m3 (4-hour exposure) (1, unconfirmed)

LD50 (oral, rat): 7060 mg/kg (41); 10600 mg/kg (41); 13660 mg/kg (37)

LD50 (oral, mouse): 3450 mg/kg (1, unconfirmed)

LD50 (oral, guinea pig): 5560 mg/kg (37)

0000067-63-0 ISOPROPYL ALCOHOL

LC50 (rat): 17000 ppm (4-hour exposure); cited as 12000 ppm (8-hour exposure) (18)

LD50 (oral, male rat): 4710 mg/kg (cited as 6.0 mL/kg) (19)

LD50 (oral, mouse): 3600 mg/kg (20, unconfirmed)

LD50 (dermal, rabbit): 12870 mg/kg (cited as 16.4 mL/kg) (14)

0000078-93-3 METHYL ETHYL KETONE

LC50 (male rat): 11,700 ppm (4-hour exposure) (3)

LC50 (male rat): 11,300 ppm (4-hour exposure); cited as 23.5 mg/L (7,990 ppm) (8-hour exposure) (4)

LD50 (oral, adult male rat): 2,740 mg/kg; cited as 3.4 mL/kg (1)

LD50 (dermal, rabbit): greater than 5,000 mg/kg (29)

0000109-60-4 N-PROPYL ACETATE

LD50 (oral, rat): 8700 mg/kg; cited as 9.8 mL/kg (4)

LD50 (oral, mouse): 8300 mg/kg (5)

LD50 (oral, rabbit): 6600 mg/kg; cited as 65 mmols/kg (6)

LD50 (dermal, rabbit): Greater than 17700 mg/kg; cited as 20 mL/kg (4)

0000141-78-6 ETHYL ACETATE

LC50 (rat): 19600 ppm (4-hour exposure); cited as 16000 ppm (6-hour exposure) (10)

LC50 (mouse): 10600 ppm (38100 mg/m3) (4-hour exposure); cited as 44000 mg/m3 (3-hour exposure) (8)

LD50 (oral, rat): 10200 mg/kg (cited as 11.3 mL/kg) (7); 5600 mg/kg (5,13)

LD50 (oral, mouse): 4100 mg/kg (11)

LD50 (oral, rabbit): 4900 mg/kg (9)

LD50 (oral, guinea pig): 5500 mg/kg (11)

LD50 (dermal, rabbit): Greater than 18000 mg/kg (cited as 20 m

---

## SECTION 12) ECOLOGICAL INFORMATION

---

### Toxicity

No Data Available

### Persistence and Degradability

Product is not expected to persist in the environment.

---

## SECTION 13) DISPOSAL CONSIDERATIONS

---

### Waste Disposal

Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes.

COMPONENTS SUBJECT TO US EPA LAND DISPOSAL RESTRICTIONS: Contains Chromium (CAS : 7440-47-3).

---

## SECTION 14) TRANSPORT INFORMATION

---

### U.S. DOT Information

Hazard Class: 3

See 49CFR 172.101 for Special Provisions, Packaging, and QTY Limitations.

Paint, 3, UN 1263, PG II, ERG GUIDE 128

#### IMDG Information

Paint, 3, UN 1263, PG II, ERG GUIDE 128

Hazard Class: 3

Marine Pollutant: No data available.

#### IATA Information

Hazard Class: 3

Paint, 3, UN 1263, PG II, ERG GUIDE 128

---

## SECTION 15) REGULATORY INFORMATION

---

CAS	Chemical Name	% By Weight	Regulation List
0000064-17-5	ETHYL ALCOHOL	31% - 51%	SARA312,VOC,TSCA
0000078-93-3	METHYL ETHYL KETONE	24% - 39%	CERCLA,SARA312,VOC,TSCA
NA-Proprietary	PolyKetone Resin	8% - 20%	SARA312
0000067-63-0	ISOPROPYL ALCOHOL	4% - 9%	SARA312,VOC,IARCCarcinogen,TSCA
0000141-78-6	ETHYL ACETATE	0.2% - 3%	CERCLA,SARA312,VOC,TSCA
0007440-48-4	COBALT	0.1% - 1.7%	SARA313, CERCLA,HAPS,SARA312,IARCCarcinogen,TSCA,CA_Prop65 - California Proposition 65,CA_Prop65_Type_Toxicity_Cancer - CA_Proposition65_Type_Toxicity_Cancer
0007440-47-3	CHROMIUM	0.1% - 1.2%	SARA313, CERCLA,HAPS,SARA312,IARCCarcinogen,TSCA
0000109-60-4	N-PROPYL ACETATE	0.1% - 0.9%	SARA312,VOC,TSCA

---

## SECTION 16) OTHER INFORMATION

---

### Glossary

ACGIH- American Conference of Governmental Industrial Hygienists; ANSI- American National Standards Institute; Canadian TDG- Canadian Transportation of Dangerous Goods; CAS- Chemical Abstract Service; Chemtrec- Chemical Transportation Emergency Center (US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC- Equivalent Concentration; EH40 (UK)- HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA- Emergency Planning and Community Right-To-Know Act; ESL- Effects screening levels; HMIS- Hazardous Material Information Service; LC- Lethal Concentration; LD- Lethal Dose; NFPA- National Fire Protection Association; OEL- Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL- Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act; SARA 313- Superfund Amendments and Reauthorization Act, Section 313; SCBA- Self-Contained Breathing Apparatus; STEL- Short Term Exposure Limit; TCEQ- Texas Commission on Environmental Quality; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA- Time Weighted Value; US DOT- US Department of Transportation; WHMIS- Workplace Hazardous Materials Information System.

### OTHER

COMPANY INFORMATION: THIS INFORMATION IS FURNISHED WITHOUT WARRANTY, EXPRESSED OR IMPLIED, EXCEPT THAT IS ACCURATE TO THE BEST KNOWLEDGE OF TOUCH-UP SOLUTIONS LLC.

COMPANY DISCLAIMER: THE DATA ON THIS SHEET RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED HEREIN. TOUCH-UP SOLUTIONS LLC ASSUMES NO LEGAL RESPONSIBILITY FOR USE OR RELIANCE UPON THIS DATA.

Part 1: The information contained in this SDS was obtained from current and reliable sources, however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy.

Part 2: Since the conditions or handling, storage and disposal of this product are beyond the control of Touch-Up Solutions LLC. Touch-Up Solutions LLC will not be responsible for loss, injury, or expense arising out of the products improper use.

Part 3: No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS.



Part 4: Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.

**Version 1.0:**

Revision Date: Feb 14, 2018

Version 1.0

---

**DISCLAIMER**

Touch-Up Solutions, Inc. to the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.