

Installation Instructions

Secondary Amplifier Kit for NGX Infinity Kit #26679606

These instructions outline the procedures to install a Secondary Amplifier in your NGX Infinity jukebox.

Tools Required – 1/4+Nut Driver

Parts Included with this Kit:

<u>Item #</u>	<u>Part Number</u>	<u>Description</u>	<u>Quantity</u>
1	34113101	Harness - Interconnect	1
2	40991408	Secondary Amplifier	1
3	86663610	#8 x 5/8+Hex Head Wood Screw	2
		These Instructions	

Caution: Power off the jukebox and wait for the Rail Voltage LEDs to go out before installing the Secondary Amplifier.

1. Plug one end of the Interconnect harness into the connector on the back of the Secondary Amplifier.
2. Install the Secondary Amplifier as shown to the right. Use the two wood screws installing them into the pilot holes provided in the side of the jukebox cabinet.
3. Connect the free end of the Interconnect harness to the Primary Amplifier. Be sure the connectors are full seated.
4. Make connections to your extension speakers or install a second Audio Output Transformer (Kit #22180807) and connect the transformer wiring to the secondary amplifier.
5. Power up the jukebox and check operation of your extension speakers. See *Section C – Sound System Set Up* in the NGX Infinity Service Manual for information on choosing and connecting extension speakers.

