

# HEALTHIERCHOICE®

## 100% HIGH DENSITY MEMORY FOAM CARPET CUSHION

### DESCRIPTION

Premium 100% high density memory foam cushion for use under all carpet styles.

### STYLE / SKU / ROLL SPECS

BGE270 – 6' x 45' roll, 270 sq. ft., 30 sq. yd. (78 lbs.)

### MATERIAL

Frothed polyurethane – a visco-elastic “memory foam” material.

### THICKNESS

0.25" (1/25")

### DENSITY

10lbs/ft<sup>3</sup> (48.82kg/m<sup>3</sup>)

### SOUND RATING

Impact Insulation Class (ASTM E492-90) ..... 75 IIC

### WATER RESISTANCE

British Spill Test Method E ..... Pass  
Breathable Integral Skin Barrier, allows vapor to pass while blocking liquid spills, making clean-up easier and more effective.

### INSULATION RATING

R-Factor (ASTM C518-10) ..... 0.90  
Excellent for radiant heated floors.

### FIRE RATING

NBS Smoke Chamber ..... <100 max  
Pill Test (FF 1-70) ..... Pass

### DURABILITY

Compression Set ..... 7% max  
Indentation Load Deflection (25%) ..... 8.00 lbs/ft<sup>2</sup>  
Indentation Load Deflection (65%) ..... 39.00 lbs/ft<sup>2</sup>

### INSTALLATION

Engineered for stretch-in installation. Install foam side up.

### WARRANTY

Warranted for a lifetime to the original purchaser.

### RENEWABLE CONTENT

IMade in part with eco-friendly soybean oil, lessening dependence on petrochemicals. This reduces global warming emissions and the need for foreign oil while supporting local farmers and local producers. Applicable towards LEED Credit MR 6 – Rapidly Renewable Resources.

### INDOOR AIR QUALITY

CRI Green Label certified. The only carpet cushion GREENGUARD Indoor Air Quality Certified® as a low emitting interior building material. Applicable towards LEED Credit EQ 4.3 – Low Emitting Product.

### ANTIMICROBIAL

Ultra-Fresh® Antimicrobial prevents mold, mildew, and bacterial growth while controlling dust mites for life-long odor free installation.

### RECYCLABLE

Zero-Landfill Manufacturing waste, all materials are reused in products with recycled content. Post consumer recyclable, a valued commodity as recycled foam in the manufacturing of rebond padding.

**NOTE: Specification values subject to a 7% manufacturing tolerance.**

## HC BEIGE



6' X 45' ROLL



14"  
ROLL DIAMETER  
CORE SIZE: 3.625"

